



Industrial Tools



- ▶ *Fast, accurate, reliable*
- ▶ *Long life, low maintenance*
- ▶ *Wide adjustable torque range*
- ▶ *Highly user-friendly*

Impulse Range

The Ultimate Power Tools

More than just a new tightening experience...





Quiet and virtually vibration-free, the CP Impulse Tool gives a smooth, rapid rundown, leveling off at precisely the preset torque with a high level of accuracy and repeatability. With their advanced ergonomic design, CP Impulse Tools are extremely operator-friendly. They're light and well-balanced, with comfortable rubber grips. Power-to-weight ratios are high – reaction forces are low.


Why choose CP Impulse Tools?

- **High speed operation** - Using a CP Impulse Tool will speed up your process and boost productivity.
- **Less maintenance, longer service life** - With very few moving parts, CP Impulse Tools require less servicing, and maintenance costs are low.
- **Low reaction forces** - While minimizing the physical impact of the tool on the operator, low reaction forces also contribute to consistent end-product quality.
- **They have the Ergo Touch!** With their high torque output to weight ratios and low noise and vibration levels, CP Impulse Tools are highly operator-friendly. This protects operator health and raises productivity in your plant.

Choose your tool



High performance – low maintenance



Lubrication-free, twin chamber air motor provides high torque and fast rundown.

Rubber grip insulates the hands from cold and ensures operator comfort.

Patented shut-off system with inertia-absorbing body provides high accuracy, minimizes operator fatigue.

Patented pulse unit with cam-guided pistons and rollers provides high torque output and low weight.

Two-step trigger for easy bolt positioning and operator comfort.


Advanced silencer includes a patented adjustable valve that gives high performance on hard joints at low torque levels.

Shut Off or Non Shut Off?




Shut Off impulse tools automatically provide the highest level of accuracy and repeatability, irrespective of operator skill.

Non Shut Off versions are suitable for applications where it is advantageous for the operator to control the process.



Very few moving parts In CP Impulse Tools the use of pulse technology reduces wear and eliminates the risk of broken springs. The tools are easy and economical to service and maintenance costs are low.

High accuracy on hard joints



Shut Off tools are equipped with an advanced silencer with a patented adjustable valve. During the rundown phase, the speed is decreased by means of a back pressure created by the adjustable valve. The slow rundown creates less energy and consequently improves accuracy on hard joints at low torque levels.



Impulse – Shut Off and Non Shut Off


5 to 450 Nm (4 to 332 ft.lb) – 1,900 to 10,000 rpm



ACCESSORIES INCLUDED

PART NO.

- Air hose nipple
 - Screwdriver adjustment for all models, except PT031/070/110160/240
- 205 050 137 3



OPTIONAL ACCESSORIES

PART NO.

- Reporting Kit for PT010/014/025L 205 050 174 3
- Suspension bail for PT031/010/014/025L 451463
- Suspension bail for PT031/052/010/014T 451393
- Suspension bail for PT070/110/025/040/070/125T 459843
- Suspension bail for PT160/240T 205 050 998 3
- Suspension bail for PT250/450T 205 050 906 3
- Exhaust hose for PT031L 452243
- Exhaust hose for PT010/014/025L 459813

PIC REF	MODEL	PART NUMBER	FREE SPEED	OUTPUT DRIVE	TORQUE RANGE		DIMENSIONS				WEIGHT	AIR FLOW		HOSE INT. DIA.				
					rpm	in	Nm	ft.lb	L	X		H	kg	lb	l/s	cfm	mm	in
NON SHUT OFF																		
A	PT031-L10000-I10S	205 147 466 4	10000	Sq 3/8	20-31	15-23	221	8.7	22	0.87	-	-	0.7	1.5	8	17	8	5/16
B	PT031-T9000-I10S	205 147 467 4	9000	Sq 3/8	20-31	15-23	152	6.0	22	0.87	175	6.9	0.8	1.8	8	17	8	5/16
C	PT052-T7000-I10S	205 147 468 4	7000	Sq 3/8	30-52	22-38	174	6.9	23	0.90	175	6.9	1.0	2.0	9	19	10	3/8
C	PT070-T6000-I13S	205 147 469 4	6000	Sq 1/2	50-70	37-52	168	6.6	26	1.02	190	7.5	1.3	2.9	11	23	10	3/8
C	PT110-T4500-I13S	205 147 470 4	4500	Sq 1/2	65-110	48-81	178	7.0	29	1.14	198	7.8	.6	3.5	2	25	10	3/8
D	PT160-T3500-I13S	205 147 471 4	3500	Sq 1/2	110-160	81-118	188	7.4	34	1.34	209	8.2	2.4	5.3	14	30	13	1/2
E	PT240-T2800-I19S	205 147 472 4	2800	Sq 3/4	160-240	118-177	205	8.1	37	1.46	212	8.3	3.3	7.3	15	32	13	1/2
SHUT OFF																		
B	PT010-T5500-S4Q	205 146 227 4	5500	Hex 1/4	5-10	4-7	205	8.1	21	0.8	178	7.0	0.95	2.1	6	13	8	5/16
F	PT010-L5000-S4Q	205 146 225 4	5000	Hex 1/4	5-10	4-7	212	8.3	21	0.83	-	-	0.9	1.9	6	13	8	5/16
B	PT014-T6000-S4Q	205 146 228 4	6000	Hex 1/4	8-14	6-10	205	8.1	21	0.83	178	7.0	1.0	2.2	6	13	8	5/16
F	PT014-L6000-S4Q	205 146 226 4	6000	Hex 1/4	8-14	6-10	212	8.3	21	0.83	-	-	0.9	2.0	6	13	8	5/16
G	PT025-T4500-S10S	205 147 462 4	4500	Sq 3/8	13-25	10-18	177	7.0	26	1.02	192	7.6	1.3	2.9	7	15	8	5/16
H	PT025-L4500-S10S	205 147 463 4	4500	Sq 3/8	13-25	10-18	236	9.3	25	0.98	-	-	1.2	2.5	7	15	8	5/16
G	PT040-T6000-S10S	205 146 229 4	6000	Sq 3/8	22-40	16-29	177	7.0	26	1.02	192	7.6	1.4	3.0	8	17	8	5/16
J	PT070-T4000-S13S	205 146 230 4	4000	Sq 1/2	32-70	24-51	192	7.6	29	1.14	200	7.9	1.8	4.0	10	21	10	3/8
J	PT125-T3500-S13S	205 146 231 4	3500	Sq 1/2	62-125	48-92	201	7.9	34	1.34	211	8.3	2.4	5.3	12	25	10	3/8
K	PT250-T2200-S19S	205 147 464 4	2200	Sq 3/4	25-250	92-185	216	8.5	37	1.46	215	8.5	3.3	7.2	20	42	13	1/2
L	PT450-T1900-S19S	205 147 465 4	1900	Sq 3/4	225-450	166-332	202	8.0	42	1.65	229	9.0	4.3	9.5	22	46	13	1/2



1-800-353-4676 A Lou Zampini & Associates Website

PneumaticToolsOnline.Com

Proud distributors of Chicago Pneumatic, Desoutter, and Georges Renault

