

Angle Head - Shut off

Lou Zampini & Associates
 2 Douglas Pike
 Smithfield, RI 02917
 401 354 8878, 1800 353 4676
 FAX 401 353 0113

0.4 to 120 Nm (3.5 to 1062 in.lb) - 190 to 2200 rpm

<http://www.LouZampini.com>
<http://www.PneumaticToolsOnline.com>



See page 70

Accessories: see page 84 

PIC REF	MODEL	PART NUMBER	FREE SPEED	OUTPUT	TORQUE RANGE		FITTED SPRING		LENGTH		WEIGHT		AIR FLOW		AIR INLET	HOSE INT.	
					rpm	in.	Nm	in.lb	Nm	in.lb	mm	in.	kg	lb.	l/s	cfm	in.
TWO WAY																	
A	SC021-L2000-S90A4S	1459154	2000	1/4 sq	0.4-2.1	3.5-18.6	0.4-0.9	3.5-7.9	275	10.8	0.84	1.85	6.5	13.8	1/8	6	1/4
A	SC021-L1400-S90A4S	1459144	1400	1/4 sq	0.4-2.1	3.5-18.6	0.6-2.1	5.3-18.6	275	10.8	0.84	1.85	6.5	13.8	1/8	6	1/4
A	SC043-L950-S90A4S	1459134	950	1/4 sq	0.4-4.3	3.5-38.0	0.9-4.3	7.9-38.0	275	10.8	0.84	1.85	6.5	13.8	1/8	6	1/4
A	SC047-L500-S90A4S	1459124	500	1/4 sq	0.4-4.7	3.5-41.5	0.9-4.7	7.9-41.5	275	10.8	0.84	1.85	6.5	13.8	1/8	6	1/4
B	SC021-L2200-S45A4S	1459574	2200	1/4 sq	0.4-2.1	3.5-18.6	0.4-0.9	3.5-7.9	339	13.3	0.85	1.87	6.5	13.8	1/8	6	1/4
B	SC021-L1500-S45A4S	1459584	1500	1/4 sq	0.4-2.1	3.5-18.6	0.6-2.1	5.3-18.6	339	13.3	0.85	1.87	6.5	13.8	1/8	6	1/4
B	SC043-L1050-S45A4S	1459594	1050	1/4 sq	0.4-4.3	3.5-38.0	0.9-4.3	7.9-38.0	339	13.3	0.85	1.87	6.5	13.8	1/8	6	1/4
B	SC047-L520-S45A4S	1459604	520	1/4 sq	0.4-4.7	3.5-41.5	0.9-4.7	7.9-41.5	339	13.3	0.85	1.87	6.5	13.8	1/8	6	1/4
B	SC021-L2200-S45A4H	1459484	2200	1/4 hex	0.4-2.1	3.5-18.6	0.4-0.9	3.5-7.9	339	13.3	0.84	1.85	6.5	13.8	1/8	6	1/4
B	SC021-L1500-S45A4H	1459494	1500	1/4 hex	0.4-2.1	3.5-18.6	0.6-2.1	5.3-18.6	339	13.3	0.84	1.85	6.5	13.8	1/8	6	1/4
B	SC043-L1050-S45A4H	1459504	1050	1/4 hex	0.4-4.3	3.5-38.0	0.9-4.3	7.9-38.0	339	13.3	0.84	1.85	6.5	13.8	1/8	6	1/4
B	SC047-L520-S45A4H	1459514	520	1/4 hex	0.4-4.7	3.5-41.5	0.9-4.7	7.9-41.5	339	13.3	0.84	1.85	6.5	13.8	1/8	6	1/4
C	SC021-L2000-S90A4H	1459074	2000	1/4 hex	0.4-2.1	3.5-18.6	0.4-0.9	3.5-7.9	275	10.8	1.12	2.47	6.5	13.8	1/8	6	1/4
C	SC021-L1400-S90A4H	1459064	1400	1/4 hex	0.4-2.1	3.5-18.6	0.6-2.1	5.3-18.6	275	10.8	1.12	2.47	6.5	13.8	1/8	6	1/4
C	SC043-L950-S90A4H	1459054	950	1/4 hex	0.4-4.3	3.5-38.0	0.9-4.3	7.9-38.0	275	10.8	1.12	2.47	6.5	13.8	1/8	6	1/4
C	SC047-L500-S90A4H	1459044	500	1/4 hex	0.4-4.7	3.5-41.5	0.9-4.7	7.9-41.5	275	10.8	1.12	2.47	6.5	13.8	1/8	6	1/4
D	SD070-LB1100-S90-A4H	1463254	1100	1/4 hex	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.12	2.47	8.7	18.4	1/4	10	3/8
D	SD070-LB820-S90-A4H	1463244	820	1/4 hex	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.12	2.47	8.7	18.4	1/4	10	3/8
D	SD070-LB510-S90-A4H	1463234	510	1/4 hex	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.12	2.47	8.7	18.4	1/4	10	3/8
D	SD070-LB320-S90-A4H	1463224	320	1/4 hex	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.12	2.47	8.7	18.4	1/4	10	3/8
D	SD070-LR1100-S90-A4H	1463294	1100	1/4 hex	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LR820-S90-A4H	1463284	820	1/4 hex	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LR510-S90-A4H	1463274	510	1/4 hex	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LR320-S90-A4H	1463264	320	1/4 hex	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LB1100-S90-A4S	1463374	1100	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LB820-S90-A4S	1463364	820	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LB510-S90-A4S	1463354	510	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LB320-S90-A4S	1463344	320	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LR1100-S90-A4S	1463414	1100	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LR820-S90-A4S	1463404	820	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LR510-S90-A4S	1463394	510	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LR320-S90-A4S	1463384	320	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	305	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD070-LR160-S90-A4S	205 146 705 4	160	1/4 sq	2.5-7.0	22.0-61.9	2.5-7.0	22.0-61.9	306	12.0	1.11	2.45	8.7	18.4	1/4	10	3/8
D	SD072-LB1080-S90-A10S	1463504	1080	3/8 sq	2.5-7.2	22.0-63.7	2.5-7.2	22.0-63.7	353	13.9	1.41	3.11	8.7	18.4	1/4	10	3/8
E	SD095-LB800-S90-A10S	1463494	800	3/8 sq	3.0-9.5	26.6-84.1	3.0-9.5	26.6-84.1	353	13.9	1.41	3.11	8.7	18.4	1/4	10	3/8
E	SD130-LB600-S90-A10S	1463484	600	3/8 sq	4.5-13.0	39.8-115.0	4.5-13.0	39.8-115.0	353	13.9	1.41	3.11	8.7	18.4	1/4	10	3/8
E	SD209-LB370-S90-A10S	1463474	370	3/8 sq	6.0-20.9	53.1-185.0	6.0-20.9	53.1-185.0	376	14.8	1.50	3.31	8.7	18.4	1/4	10	3/8
E	SD300-LB250-S90-A10S	1463464	250	3/8 sq	11.0-30.0	97.3-265.5	11.0-30.0	97.3-265.5	376	14.8	1.50	3.31	8.7	18.4	1/4	10	3/8
E	SD072-LR1080-S90-A10S	1463554	1080	3/8 sq	2.5-7.2	22.0-63.7	2.5-7.2	22.0-63.7	376	14.8	1.41	3.11	8.7	18.4	1/4	10	3/8
E	SD095-LR800-S90-A10S	1463544	800	3/8 sq	3.0-9.5	26.6-84.1	3.0-9.5	26.6-84.1	376	14.8	1.41	3.11	8.7	18.4	1/4	10	3/8
E	SD130-LB600-S90-A10S	1463534	600	3/8 sq	4.5-13.0	39.8-115.0	4.5-13.0	39.8-115.0	376	14.8	1.41	3.11	8.7	18.4	1/4	10	3/8
E	SD209-LR370-S90-A10S	1463524	370	3/8 sq	6.0-20.9	53.1-185.0	6.0-20.9	53.1-185.0	376	14.8	1.41	3.11	8.7	18.4	1/4	10	3/8
E	SD300-LR250-S90-A10S	1463514	250	3/8 sq	11.0-30.0	97.3-265.5	11.0-30.0	97.3-265.5	376	14.8	1.50	3.31	8.7	18.4	1/4	10	3/8
E	SD300-LR180-S90-A10S	205 146 704 4	180	3/8 sq	11.0-30.0	97.3-265.5	11.0-30.0	97.3-265.4	375	14.8	1.50	3.30	8.7	18.4	1/4	10	3/8
F	SH500-LR330-S90-A13S	205 147 473 4	330	1/2 sq	25.0-50	221-442	25.0-50	221-442	453	17.8	2.20	4.8	16.0	34.0	1/4	10	3/8
F	SH700-LR225-S90-A13S	205 147 474 4	225	1/2 sq	34.0-70	301-619	34.0-70	301-619	487	19.2	2.40	5.3	16.0	34.0	1/4	10	3/8
F	SH850-LR190-S90-A13S	205 147 475 4	190	1/2 sq	40.0-85	354-752	40.0-85	354-752	530	20.8	2.80	6.1	16.0	34.0	1/4	10	3/8
F	SH1200-LR215-S90-A13S	205 147 476 4	215	1/2 sq	70.0-120	620-1062	70.0-120	620-1062	590	23.2	3.50	7.6	28.0	59.0	1/2	13	1/2

